

Wash Select II[®] by Unitec

Simplify Car Wash Transactions

DRB[™]
In-Bay
Solutions

Hardware

The Wash Select II is a quality entry system for the unattended automatic car wash market. As the reliable car wash entry system for the petroleum market, its patented, ergonomically-designed front features daylight-readable LCD displays that guide customers through the car wash payment process while promoting the purchase of upgrades.

Customer Convenience

Using the Wash Select II to choose and pay for a car wash is simple. Options and costs are clearly presented and can be selected with the simple press of a button.

Marketing Options

Programming options allow car wash owners to promote up to three services (such as wax, tire shine, etc.). These features allow a site owner to upsell and ultimately increase revenue. Custom overlays are also available for Wash Select II units, both new and in the field.

POS4000

When paired with a POS4000/V2, customers may also purchase washes at a gas pump or in the C-Store. The POS4000 offers additional selling capabilities and accounting controls that help to maximize profits. The Remote POS4000 feature allows you to issue unique codes at up to four remote locations, which is a great way to partner with local businesses.



by **Unitec**

WashPay Interface

Enhance the functionality of your Wash Select II by adding a WashPay Site Controller, providing integrated reporting for revenue, accounting and pricing. This enhancement also increases marketing capabilities with additional “house account” options and promotions.

Security

The Wash Select II's heavy gauge stainless steel door and security bar work to keep profits secure. Optional alarm and camera surveillance systems are also available.

DRB[™]

www.DRB.com
443.561.1200

Features

Hardware Features

- Durable metallic keypad for code entries
- Wash selection
- In-Bay Automatic and tunnel compatible
- VIP Wash Coupon acceptance
- Customer proximity/drive-up sensor
- Mars bill validator
- Accepts \$1, \$5, \$10 and \$20 bills
- SLUGBUSTER® II coin acceptor for quarters
- 2,500 coin hopper capacity
- Integrated alarm switch (for connection to existing site alarm system)

Software Features

- 350 programmable fleet accounts (codes only)
- Enhanced fleet account software, including VIP Wash Pass acceptance and 1,000 fleet accounts or coupon codes
- Up to four programmable wash packages
- Optional sales feature allows for the sale of up to three additional services (wax, tire shine, etc.)
- Detailed accounting reports by cash, coupons, credit, token and fleet
- Quick set-up of fleet accounts by use of profiles
- Passcodes/cards for accessing system functions without opening door
- Credit receipts (with optional credit card acceptance and optional printer)

- Customizable greeting message
- Programmable ticket messages can include header, footer, special wash instructions and promotional notices
- Coupon codes for mailing and promotions
- Cash receipts (with optional printer)

Optional Features

- EMV and contactless payment solutions
- Visa®, Mastercard®, American Express® and Discover® acceptance via internet connection
- Credit processing through Verifone or Gilbarco (mag stripe only)
- Dual-sided card reader (needed for VIP Wash Pass, included in credit option)
- IDX-X10 multi-coin acceptance—quarters, \$1 coins and up to four types of tokens (coin diameter from .9" to 1.25")
- Tunnel Start Button
- WashPay® interface
- Integrated alarm system
- Thermal receipt and report printer
- Multi-unit fleet sharing capability (max 1,000 sharable accounts)
- Barrier gate (manages traffic control and assures accuracy of the wash queue)
- Line conditioner and surge suppressor
- Custom overlays offer exceptional branding opportunities

Specifications

Size & Shipping Weight:

- Case: 23.6" H x 17.74" W x 19.25" D | 150 lbs.
- Std. Base: 32.5" H x 17.75" W x 9.5" D | 80 lbs.
- Curb Base: 26" H x 17.75" W x 9.5" D | 70 lbs.
- Angled Std. Base: 32" H x 17.75" W x 9.75" D | 90 lbs.
- Angled Curb Base: 26" H x 17.75" W x 9.75" D | 80 lbs.
- Overall Depth Angled Base: 30"

Operating Temperatures:

- Certified -20° F — 115° F
- Brick-in recommended for units operating at sustained periods below 0° F and above 100° F

Electrical:

- 120 VAC grounded with 5 amp dedicated circuit breaker (16-18 AWG)
- Wiring to car wash controller—typically 3+1 per wash type (16-18 AWG)
- CAT5 cable required for credit processing and WashPay integration options

Warranty

One-year limited warranty from date of purchase



For more information, contact us at 443.561.1200
www.DRB.com

